

RUVINOL®

PRODUCT DATA

No. Document : DC.RD.DF.08
 No. Reference : 1300-SC
 Edition : A
 Revise : 1
 Release Date : 03/08/2006
 Page : 1



SOLVENT-BASED ROOF PAINT

CHARACTERISTICS

Special Properties & Advantages

- Excellent adhesion and film properties.
- Good weathering and color durability.
- Protect roof tile against extremely weather condition.

Composition

An Acrylic thermoplastic and good weather resistance pigment

SPECIFICATION

Code

GT – SB – 1300 – XXXX

Color

See appropriate Color Card, available in other colors

Specific Gravity

1.00 ± 0.10 (depend on color)

Solid Content

30 – 36 (by volume, depend on color)

Spreading Rate

3 – 4 m²/kg

APPLICATION

Intended Use

Roof tile, concrete, cement,

Surface Preparation

Surface to be painted must be clean, dry and free of dust, dirt and grease.

Direction

- Stir gently and dilute with Thinner TH-GT-0313-0001.
- 30 – 50% by brush, 50 – 100% by spray
- Apply evenly and generously by brush or spray.

Drying Time

At room temperature 30° C and standard thickness.

- Dust free : 5 - 10 minutes.
- Tack free : 2 – 3 hours.

PACKAGING

Packing

5 kg and 20 kg.

Shelf Life

1 year in original pack and store in good ventilated room.

PRECAUTION

Safety

Avoid contact with eyes and inhalation of mists when using a spray gun. Close container tightly after use.