

**RUVINOL®**

## PRODUCT DATA

No. Document : DC.RD.DF.08  
 No. Reference : 1360-XXXX  
 Edition : A  
 Revise : 2  
 Release Date : 03/08/2006  
 Page : 1



*inspirasi dalam warna*

## WATER-BASED ROOF PAINT

### CHARACTERISTICS

#### Special Properties & Advantages

- High quality roof paint to protect & beautify the roof.
- Resistant to alkali and fungus.
- Protect roof tile against extremely weather condition .
- Resistant to Ultra Violet Light degradation.
- Excellent adhesion and film properties.

#### Composition

An Acrylic copolymer emulsion.

### SPECIFICATION

#### Code

GT – WB – 1360 – XXXX

#### Color

See appropriate Color Card, available in other colors

#### Specific Gravity

1.00 ± 0.1 ( depend on color )

#### Solid Content

28 – 39 % ( by volume, depend on color )

#### Spreading Rate

3 – 4 m<sup>2</sup>/kg

### APPLICATION

#### Intended Use

Suitable for concrete and other roof substrate.

#### Surface Preparation

Surface to be painted must be clean, dry and free of dust, dirt and grease. Applied 2 coats to ensure maximum durability, the first coat should be applied at low viscosity to ensure good penetration.

#### Direction

- Stir gently and dilute with Water.  
20 – 30% by brush, 50% by spray
- Apply evenly and generously by brush or spray.

#### Drying Time

At room temperature 30° C and standard thickness.  
 • Tack free : 20 – 30 minutes

### PACKAGING

#### Packing

5 kg and 20 kg.

#### Shelf Life

1 year in original pack and store in good ventilated room.

### PRECAUTION

#### Safety

Avoid contact with eyes and inhalation of mists when using a spray gun. Close container tightly after use.