



PRODUCT DATA

No. Document : DC.RD.DF.08
 No. Reference : 1600-SC
 Edition : B
 Revise : 0
 Release Date : 15/08/2008
 Page : 1



ROAD MARKING PAINT

CHARACTERISTICS	Special Properties & Advantages	<ul style="list-style-type: none"> • Good weather resistant and abrasion resistance. • Easy to apply. • Available in Reflective and Non-reflective.
	Composition	An Acrylic thermoplastic and good abrasion resistance pigment
SPECIFICATION	Code	SD - SC – 1600 – XXXX
	Color	White, Yellow
	Specific Gravity	1.28 ± 0.05 (White, other color may vary)
	Solid Content	67 ± 1 % (by weight) 39 ± 1 % (by volume)
	Spreading Rate	2 – 3 m ² /kg (at 150 – 200 μ DFT)
APPLICATION	Substrate	Road, cement.
	Equipment	Brush, Normal Spray Gun, Airless Spray.
	Dilution	10 - 20% with Thinner TH-SD-0316-0001.
	Drying Time	At room temperature 30° C and standard thickness. <ul style="list-style-type: none"> • Dust free : 5-10 min. • Tack free : 50-60 min.
	Additional	For Reflective type pure with the glass bead SD-161 (a surface application rate of 300-400 gr/m ² is recommended for maximum reflectivity and durability)
PACKAGING	Packing	20 kg
	Shelf Life	1 year in original pack and store in good ventilated room.
PRECAUTION	Safety	Avoid contact with eyes and inhalation of mists when using a spray gun. Close container tightly after use.

The Information given above is based upon our practical knowledge and experience, but, for improvement of product, is subject to change without prior notice. Due to different materials or substrates use as well as to varying working conditions which are beyond our control, we strictly recommended to carry out trials and to consult our technicians. PT. Putramataram CI guarantees the constancy of the products.