



# PRODUCT DATA

No. Document : DC.RD.DF.08  
 No. Reference : 3205-XXXX  
 Edition : B  
 Revise : 0  
 Release Date : 17/07/2007  
 Page : 1 of 2



## ACRYL PRO

<b>CHARACTERISTICS</b>	<b>Special Properties &amp; Advantages</b>	<ul style="list-style-type: none"> <li>• Excellent adhesion and film properties.</li> <li>• Good weathering and color durability.</li> <li>• Protect substrate against extremely weather condition.</li> <li>• Can be applied on substrate directly without a primer.</li> </ul>
	<b>Composition</b>	An Acrylic thermoplastic and good weather resistance pigment.
<b>SPECIFICATION</b>	<b>Code</b>	<b>AC – MF – 3205 – XXXX</b>
	<b>Color</b>	Various *
	<b>Specific Gravity</b>	1.04 ± 0.05 (for White, other color may vary)
	<b>Solid Content</b>	40 ± 2 % (by weight)
	<b>Spreading Rate</b>	9 m2/kg (at 40 µ DFT) one coat.
<b>APPLICATION</b>	<b>Intended Use</b>	<ul style="list-style-type: none"> <li>• Galvanize, aluminum, metal non ferrous substrate</li> </ul>
	<b>Surface Preparation</b>	<ul style="list-style-type: none"> <li>• Surfaces to be painted must be clean, dry and free of dust, dirt and grease.</li> </ul>
	<b>Directions</b>	<ul style="list-style-type: none"> <li>• Stir gently and dilute with Thinner ;            By spray : TH – AK – 0305 – 0002 (50 – 100%)            By brush : TH – GT – 0313 – 0004 (10 – 20%)</li> <li>• Apply evenly and generously by brush or spray.</li> <li>• Apply 2 coats at least.</li> </ul>
	<b>Drying Time</b>	At room temperature 30° C and standard thickness. <ul style="list-style-type: none"> <li>• Dust free : 10 – 20 minutes.</li> <li>• Tack free : 1 – 2 hours.</li> </ul>
<b>PACKAGING</b>	<b>Packing</b>	1 kg and 20 kg.
	<b>Shelf Life</b>	1 year in original pack and store in good ventilation room.
<b>PRECAUTION</b>	<b>Safety</b>	Avoid contact with eyes and inhalation of mists when using a spray gun. Close container tightly after use.

The Information given above is based upon our practical knowledge and experience, but, for improvement of product, is subject to change without prior notice. Due to different materials or substrates use as well as to varying working conditions which are beyond our control, we strictly recommended to carry out trials and to consult our technicians. PT. Putramataram CI guarantees the constancy of the products.



## PRODUCT DATA

No. Document : DC.RD.DF.08  
No. Reference : 3205-XXXX  
Edition : B  
Revise : 0  
Release Date : 17/07/2007  
Page : 2 of 2



## ACRYL PRO

\* Available colors ;

1. AC-MF-3205-1005 Signal Yellow
2. AC-MF-3205-3010 Signal Red
3. AC-MF-3205-5010 Signal Blue
4. AC-MF-3205-6005 Signal Green
5. AC-MF-3205-7005 Silver
6. AC-MF-3205-8005 Copper
7. AC-MF-3205-9005 White
8. AC-MF-3205-9905 Black