



PRODUCT DATA

No. Document : DC.RD.DF.08
No. Reference : 1010-PR
Edition : B
Revise : 0
Release Date : 1/3/2005
Page : 1



inspirasi dalam mutu

DELTA EPOXY PRIMER

CHARACTERISTICS

Special Properties & Advantages

- General purpose primer on steel.
- Long life protection against corrosion.
- Good adhesion and elasticity on the steel.

Composition

An epoxy-polyamide containing anti-corrosive pigments.

SPECIFICATION

Code

EP-PR-1010-XXXX

Color

Green or specified

Specific Gravity

1.38 ± 0.01

Solid Content

60 ± 1% (by weight)

Spreading Rate

8 m²/kg set (@ 50 µ DFT)

APPLICATION

Recommended Use

As a primer for protection of steel plates used for plants, bridges, oil tanks, steel structures, superstructure etc.

Equipment

Normal spray gun, Airless gun, Brush.

Mixing Ratio

5 l EP-PR-1010-XXXX : 1 l HD-EP-101H

Dilution

10-20% with TH-EP-0310-0001.

Drying Time

At room temperature 30°C and standard thickness.
• Touch free : 1 – 2 hours
• Pot life : 8 hours
• Full cured : 1 week
• Recoating : Minimal 4 hours. Maximum 14 days

PACKAGING

Packing

20 kg.

Shelf Life

1 year in original pack and store in good ventilation room.

PRECAUTION

Safety

Avoid contact with eyes and inhalation of mists when using a spray gun. Close container tightly after use.