



PRODUCT DATA

No. Document : DC.RD.DF.08
 No. Reference : 2690-ARP
 Edition : A
 Revise : 1
 Release Date : 27/11/2002
 Page : 1



ALKALI RESISTING PRIMER

CHARACTERISTICS	Special Properties & Advantages	<ul style="list-style-type: none"> • Good hiding power. • Odorless. • Economical.
	Composition	Styrene acrylic dispersion.
SPECIFICATION	Code	WP – DL – 2690 – 9001
	Color	White.
	Specific Gravity	1.45 ± 0.05
	Solid Content	59 ± 1 (by weight)
	Spreading Rate	5 - 6 m ² /kg
APPLICATION	Location	Interior.
	Substrate	<ul style="list-style-type: none"> • Walls and ceilings • All traditional supports : gypsum board, plasters etc. • Old paint.
	Dilution	If necessary with water (approximately 10 %).
	Equipment	Brush, Roller, Airless Spray
	Drying Time	Single coat at standard thickness. <ul style="list-style-type: none"> • Touch dry : Dependant on temperature and humidity. • Finishing : 1 to 2 hours.
PACKAGING	Packing	5 kg and 25 kg.
	Shelf Life	1 year in original pack and store in good ventilated room.
PRECAUTION	Safety	Avoid contact with eyes and inhalation of mists when using a spray gun. Close container tightly after use.