



## PRODUCT DATA

No. Document : DC.RD.DF.08  
 No. Reference : 2600-VP  
 Edition : A  
 Revise : 1  
 Release Date : 27/11/2002  
 Page : 1



## VINYLITE PLUS

### CHARACTERISTICS

#### Special Properties & Advantages

- Excellent Whiteness.
- Excellent performance.
- Good filling properties.
- Odorless.
- Very economical

#### Composition

Styrene acrylic dispersion.

### SPECIFICATION

#### Code

WP – DL – 2600 – XXXX

#### Color

White, pastel or specified

#### Specific Gravity

1.56 ± 0.05 ( for white, other color may vary )

#### Solid Content

35 ± 1 ( by volume ) ( for white, other color may vary )

#### Spreading Rate

3 - 4 m<sup>2</sup>/kg

### APPLICATION

#### Location

Interior and Exterior, but in sheltered place

#### Substrate

- Walls and ceilings
- All traditional supports : gypsum board, plasters etc.
- Old paints.

#### Dilution

- For first coat diluted with water (approximately 20%).
- For second coat or next coat diluted approximately 10% with water

#### Equipment

Brush, Roller, Airless Spray

#### Drying Time

- Single coat at standard thickness
- Touch dry : Depend on temperature and humidity.
- Recoat : 2 to 3 hours.

### PACKAGING

#### Packing

5 kg and 25 kg.

#### Shelf Life

1 year in original pack and store in good ventilated room.

### PRECAUTION

#### Safety

Avoid contact with eyes and inhalation of mists when using a spray gun. Close container tightly after use.