



# PRODUCT DATA

No. Document : DC.RD.DF.08  
 No. Reference : 2690-9010  
 Edition : B  
 Revise : 0  
 Release Date : 31/07/2006  
 Page : 1



## DECO PLAMUR

|                        |  |  |
|------------------------|--|--|
| <b>CHARACTERISTICS</b> | <b>Special Properties &amp; Advantages</b> | <ul style="list-style-type: none"> <li>• Easy to apply &amp; gives a smooth surface.</li> <li>• Good hiding power.</li> <li>• Quick drying and good sandability.</li> <li>• Containing fresh fruits fragrance.</li> <li>• Economical.</li> </ul> |
|                        | <b>Composition</b>                         | Special emulsion resin and Extender pigment.   |
| <b>SPECIFICATION</b>   | <b>Code</b>                                | <b>WP – DL – 2690 – 9010</b>   |
|                        | <b>Color</b>                               | White  |
|                        | <b>Specific Gravity</b>                    | 1.8 ± 0.05   |
|                        | <b>Solid Content</b>                       | 73 % ± 1 ( by weight )   |
|                        | <b>Spreading Rate</b>                      | As necessary.  |
| <b>APPLICATION</b>     | <b>Location</b>                            | Interior used only.  |
|                        | <b>Substrate</b>                           | <ul style="list-style-type: none"> <li>• Walls and ceilings</li> <li>• All traditional supports : gypsum board, plasters etc.</li> </ul>   |
|                        | <b>Equipment</b>                           | Spatula / putty knife  |
|                        | <b>Dilution</b>                            | If necessary with water (approximately 10 %).  |
|                        | <b>Drying</b>                              | Single coat at standard thickness.<br><ul style="list-style-type: none"> <li>• Recoating time : 1 to 2 hours.</li> </ul>   |
| <b>PACKAGING</b>       | <b>Packing</b>                             | 5 kg and 25 kg.  |
|                        | <b>Shelf Life</b>                          | 1 year in original pack and store in good ventilation room.  |
| <b>PRECAUTION</b>      | <b>Safety</b>                              | Close container tightly after use.   |

The Information given above is based upon our practical knowledge and experience, but, for improvement of product, is subject to change without prior notice. Due to different materials or substrates use as well as to varying working conditions which are beyond our control, we strictly recommended to carry out trials and to consult our technicians. PT. Putramataram CI guarantees the constancy of the products.