



# PRODUCT DATA

No. Document : DC.RD.DF.08  
 No. Reference : 3600-9000  
 Edition : A  
 Revise : 0  
 Release Date : 2/2/2010  
 Page : 1 of 1



*inspirasi dalam mutu*

## THERMAL REFLECTIVE PAINT - PRIMER

### CHARACTERISTICS

#### Special Properties & Advantages

- A primer that designed for FRIO Thermal Reflective Paint.
- Good hiding power.
- Water-based & Environmental friendly.
- Contain no heavy metal and other hazardous substance.
- Very good adhesion to non ferrous metal, galvalum, zincalume roof.

#### Composition

An Acrylic polymer

### SPECIFICATION

**Code** FR - PR - 3600 - 9000

**Color** White.

**Specific Gravity** 1.2 ± 0.02

**Solid Content** 45 % ± 2  
( by weight )

**Spreading Rate** 0.250 kg/m<sup>2</sup> (at 50μ DFT).

### APPLICATION

**Intended Use** Roof, wall & non ferrous metal substrate.

**Surface Preparation** Surface to be painted must be clean, dry and free of dust, dirt and grease.

**Dilution** Ready to used, if necessary with water (5 - 10%).

**Equipment** Brush / Roller, Airless Spray with 1.5 - 2 mm nozzle.

**Drying Time** At room temperature 30° C and standard thickness.  
 • Dust free : 10 - 15 minutes.  
 • Tack free : 6 - 8 hours.  
 • Recoating time : Min. 16 hours ; Max. 24 hours.

### PACKAGING

**Packing** 5 kg and 20 kg.

**Shelf Life** 1 year in original pack and store in good ventilated room.

### PRECAUTION

**Safety** Avoid contact with eyes and inhalation of mists when using a spray gun. Close container tightly after use.