



PRODUCT DATA

No. Document : DC.RD.DF.08
 No. Reference : 1010-PR
 Edition : B
 Revise : 1
 Release Date : 03/05/2005
 Page : 1



DELTA PU PRIMER

CHARACTERISTICS	Special Properties & Advantages	<ul style="list-style-type: none"> • General purpose primer on steel. • Long life protection against corrosion. • Good adhesion and elasticity on the steel.
	Composition	An epoxy-polyamide containing anti-corrosive pigments.
SPECIFICATION	Code	EP-PR-1010-XXXX
	Color	Green or specified
	Specific Gravity	1.38 ± 0.01
	Solid Content	60 ± 1% (by weight)
	Spreading Rate	8 m ² /kg set (@ 50 μ DFT)
APPLICATION	Recommended Use	As a primer for protection of steel plates used for plants, bridges, oil tanks, steel structures, superstructure etc.
	Equipment	Normal spray gun, Airless gun, Brush.
	Mixing Ratio	5 l EP-PR-1010-XXXX : 1 l HD-EP-101H
	Dilution	10-20% with TH-EP-0310-0001.
	Drying Time	At room temperature 30°C and standard thickness. <ul style="list-style-type: none"> • Touch free : 1 – 2 hours • Pot life : 8 hours • Full cured : 1 week • Recoating : Minimal 4 hours. Maximum 14 days
PACKAGING	Packing	20 kg.
	Shelf Life	1 year in original pack and store in good ventilation room.
PRECAUTION	Safety	Avoid contact with eyes and inhalation of mists when using a spray gun. Close container tightly after use.

The Information given above is based upon our practical knowledge and experience, but, for improvement of product, is subject to change without prior notice. Due to different materials or substrates use as well as to varying working conditions which are beyond our control, we strictly recommended to carry out trials and to consult our technicians. PT. Putramataram CI guarantees the constancy of the products.